

REPTAIL SM



USE FOR:

- REPAIRING ROADS
- BUILDING ROADS
- CYCLE PATHS
- RAILWAYS
- PARKING AREAS
- INDUSTRY FIELDS
- FOREST ROADS ETC...

FEATURES:

- WEIGHT 3600 KG
- WORKING THICKNESS 0 300 MM
- WORKING WIDTH 2,74 4,36 M
- TILT AUTOMATION
- FOR OVER 10 TONS LOADERS.
 TRACTORS AND DOZERS...
- TRANSPORT DIMENSIONS:
 3300* 2300* 1300 mm



SALES:
REPTAIL OY
+358 400 521631/pasi.mantynen@reptail.fi
WWW.REPTAIL.FI



REPTAIL SM



- CAPASITY OVER 800 TON/ H
- SAVING FUEL 50% COMPARING
 TO TRADITIONAL METHODS
- SAVING MATERIAL EVEN 20 %
- VERY LOW OPERATING COSTS

- MADE IN FINLAND
- WEARING PARTS MADE BY HARDOX STEEL
- HIGH QUALITY COMPONENTS
- CONTINUOUS PRODUCT DEVELOPMENT





OPTIONS:

- DOUBLE WHEELS FOR SOFT SURFACES
- AUTOMATION FOR GEOTEXTILES
- THICKNESS ADJUSTMENT 150-450 MM
- READINESS FOR MACHINE CONTROL
- JOYSTICK CONTROLLER

SALES: REPTAIL OY +358 400 521631/pasi.mantynen@reptail.fi WWW.REPTAIL.FI